

REV.	DESCRIPTION	DATE	DRAWN
A	New	14.01.2015	Ryan
B	general update	28.08.2019	Ronny
C	add Packing option "B"	27.09.2023	Cherry

Order Code
SLS-xxx-S900-xx /X

Packing
no suffix = Tray (standard)
T = Tube
B = Reel; with PickUp Cap

Plating
95 = Tin/Gold flash
96 = Tin/10μ" Gold
97 = Tin/15μ" Gold
98 = Tin/30μ" Gold
99 = Tin

No. of Pins	Dimension mm		
	A	B	C
010	20.02	17.52	10.16
014	25.10	22.60	15.24
016	27.64	25.14	17.78
020	32.72	30.22	22.86
024	37.80	35.30	27.94
026	40.34	37.84	30.48
030	45.42	42.92	35.56
034	50.50	48.00	40.64
040	58.12	55.62	48.26
050	70.82	68.32	60.96
060	83.52	81.02	73.66
064	88.60	86.10	78.74

Specifications
Electrical
Current rating: 3A max.
Insulation resistance: 1000MΩ min.
Contact resistance: 20mΩ max.
Withstanding voltage: 500V AC

Material
Contact: Brass
Plating: Sn on solder, Au on contact area
Insulator: PBT (black) UL 94V-0
Operating temperature: -55°C to +105°C



E-tec 2023 © - all rights reserved www.e-tec.asia



UNIT	mm	GENERAL TOLERANCE		DRAWN	DATE	DWG. NO.	SHEET 1/1
SCALE	Free	X.° ±	X. ±	Ryan	14.01.2015	SLS-S900	REV. C
		X.° ±	X. ±	Ronny	27.09.2023	SERIES NO.	
		.XX° ±	.XX ± 0.25	APPROVE	DATE	SLS-xxx-S900-xx/X	
		.XXX° ±	.XXX ±	Fagi	27.09.2023		

THT Box Header 2.54mm pitch
Straight dual row